# **ONSET**

## InTemp® CX603 Data Logger

InTemp Dry Ice Logger - Multiple Use Data Logger (CX603)

#### **Supported Measurements:**

Temperature



### InTemp CX603 Data Logger Specifications

| Temperature Probe            |   |
|------------------------------|---|
| Sensor Range                 | -95° to 50°C (-139° to 122°F)   |
| Accuracy                     | ±1.5°C from -95° to -40°C (±2.7°F from -139° to -40°F)<br>±1.0°C from -40° to -10°C (±1.8°F from -40° to 14°F)<br>±0.5°C from -10° to 50°C (±0.9°F from -14° to 122°F)  |
| Resolution                   | 0.013°C at 25°C (0.023°F at 77°F)   |
| NIST Calibration             | Three-point NIST calibration, probe only  |
| Cable Length                 | 1.5 m (4.92 ft)   |
| Probe Dimensions             | Food-grade stainless steel probe with blunt tip, 31.75 mm (1.25 inches) long, 4.78 mm (0.188 inches) diameter   |
| Logger                       |   |
| Logger Operating Range       | e-30° to 50°C (-22° to 122°F)   |
| Radio Power                  | 1 mW (0 dBm)  |
| Transmission Range           | Approximately 30.5 m (100 ft) line-of-sight   |
| Wireless Data Standard       | Bluetooth Low Energy (Bluetooth Smart)  |
| Туре                         | Multiple use  |
| Duration                     | 365 days  |
| Shelf Life                   | Up to 1 year  |
| Logging Rate                 | 1 second to 18 hours  |
| Battery                      | CR2450 3V lithium, not replaceable. Battery for CX602 and CX702 models lasts for duration specified when logger is used within the 1-year shelf life. Battery life for the CX603 and CX703 models is 1 year, typical with logging interval of 1 minute. Faster logging intervals, remaining connected with the InTemp app, excessive downloads, and paging may impact battery life. |
| Memory                       | 16,000 measurements   |
| Full Memory Download<br>Time | Approximately 30 seconds; may take longer the farther the device is from the logger   |
| Dimensions                   | 6.9 x 4.5 x 1.1 cm (2.71 x 1.76 x 0.42 inches)  |
| Weight                       | 25.5 g (0.90 oz)  |
| Environmental Rating         | IP65  |
| CE                           | The CE Marking identifies this product as complying with all relevant directives in the European Union (EU).  |
|                              |   |

Passed RTCA DO160G, part 21H

#### **Contact Us**

Sales (8am to 5pm ET, Monday through Friday)

- ► Email sales@onsetcomp.com
- Call 1-508-759-9500
- In U.S. toll free 1-800-564-4377
- Fax 1-508-759-9100

Technical Support (8am to 6pm ET, Monday through Friday)

- ► Contact Product Support www.onsetcomp.com/support/contact
- ► Call 1-508-759-9500
- In U.S. toll free 1-877-564-4377

Onset Computer Corporation 470 MacArthur Boulevard Bourne, MA 02532